

0.9 m | 3 ft. Sector Antenna, Slant +/-45 Polarized, 3.3 to 4.2 GHz

### SEC-3.5DPLX8-65-17



The SEC-3.5DPLX8-65-17 from RadioWaves 3.5 GHz 8-port Sector Antenna provides industry leading gain, side lobes suppression, and high front to back ratio. Available in 65° beamwidth with dual +/-45 slant polarization, this antenna works from 3.3 GHz – 4.2 GHz. The SEC-3.5DPLX8-65-17 has 17 dBi gain and is perfectly suited for macro base station or small cell deployments.

The Type N connectors make 2x2, 4x4, and 8x8 mimo configurations possible for high speeds or multiple technology deployments. The RadioWaves SEC-3.5DPLX8-65-17 antenna patterns are engineered to be symmetrical in both polarizations. The sector antenna's 17 dB side lobe suppression and superior 40 dB front-to-back- ratio allows for channel (frequency) reuse and can reach high levels of spectral efficiency in the most challenging and noisy environments.

The 3300 to 4200 MHz SEC-3.5DPLX8-65-17 pro sector antenna with 8 x N-type female connector has Universal radio brackets that are compatible with many popular radios. The antenna comes with an integrated hoisting hook for added safety and convenience. Our expert technical support and friendly, knowledgeable customer service personnel are available to assist you with your multiport macro base station antenna needs. The RadioWaves SEC-3.5DPLX8-65-17 is in stock and ready to ship the same day.

#### Features

- 16 to 17 dBi gain
- Superior port isolation, cross polarization discrimination, gain, VSWR, and front-to-back
- 3300 to 4200 MHz for world-wide markets
- 35 dB Front to Back Ratio
- Eight (8) N Female Connectors
- Heavy-duty aluminum brackets with powder coated steel hardware
- Integrated hoisting hook for added safety and convenient installation
- Universal radio bracket with quick-release slot/clip design is compatible with many AP radios

#### Applications

- 3.5 GHz Citizens Broadband Radio Service (CBRS) applications
- Extended CBRS for 4.2 GHz (EMEA and UK) use
- Wireless LAN systems & IEEE 802.16e applications
- Mobile WiMAX Wireless Internet Provider "cell" sites
- SOFDMA
- Outdoor or indoor point-to-point (PtP) or point-to-multipoint (PtMP) in CBRS band
- For use in LTE and 5G bands n42, n43, n48, n49, n52, n77 and n78
- 4x4 and 8x8 MIMO ready

## SPECIFICATIONS

### General

Antenna Type	Sector Antenna
Size, nominal	3 ft   0.9 m

Polarization	Slant 45 +/-
Standard RF Connector Type	N-Female

### Electrical

Operating Frequency Band	3.3 - 4.2 GHz
Half Power Beamwidth, Horizontal	65 degrees
Half Power Beamwidth, Vertical	8.5 degrees
Cross-Polarization Discrimination	19 dB
Front to Back Ratio (F/B)	40 dB
Gain, Low Frequency	17 dBi
Gain, Mid Frequency	17.1 dBi

Gain, High Frequency	17.2 dBi
VSWR	1.5:1
Return Loss	-14 dB
Port to Port Isolation, Max (dB)	30 dB
Electrical Downtilt, Degrees	3.5 degrees
Input Power per Port, Max (Watts)	100 Watts

### Mechanical

Fine Elevation Adjustment	+/- 5 degrees
Mounting Pipe Diameter, Min	2 inch   5.1 cm
Mounting Pipe Diameter, Max	4.5 inch   11.4 cm
Net Weight	24.2 lbs   11 kg
Wind Velocity Operational	90 mph   145 km/h

Wind Velocity Survival Rating	125 mph   201 km/h
Mechanical Configuration	SEC-3.5DPLX8
Axial Force (FA)	13 lbs   58 N
Side Force (FS)	13 lbs   58 N
Operating Temperature Range	-40 to +60 C

### Regulatory Compliance

Industry Canada Compliance	undeclared
RoHS-compliant	Yes

### Shipping Information

Package Type	Cardboard
Gross Weight	27.2 lbs   12.4 kg

Dimensions, L x W x H	48 x 12 x 8in   121.92 x 30.48 x 20.32 cm
Shipping Volume	2.7 cu ft   0.08 cu m

8 type N connectors to support MIMO Operation

TECHNICAL DRAWINGS

