

0.6m | 2ft, Grid Parabolic Reflector Antenna, Dual-Polarized, 1.71 to 4.2 GHz

MPD2-1.7-NM



The RadioWaves MPD2-1.7-NM is a high performance LTE / CBRS Mesh Parabolic Dish antenna specifically designed for cellular networks. RadioWaves' MPD2-1.7-NM has 16 to 18 dBi gain and can be used to broadcast Cellular LTE signals. The MPD2-1.7-NM operates from 1710 to 4200 MHz which is ideal for 5G, LTE, PCS, UMTS, CBRS applications including LoRA, LTE-M, and NB-IOT. The Multi-Band design of the RadioWaves MPD2-1.7-NM antenna eliminates the need to purchase different antennas for each frequency. This simplifies installations since the same antenna can be used for a wide array of telecommunication applications where wide coverage is desired.

The MPD2-1.7-NM from RadioWaves has directional patterns with Dual Slant ($\pm 45^\circ$) polarization and features 2 x Type N Male connectors. The Type N connectorized MPD2-1.7-NM antenna from RadioWaves is designed specifically for outdoor operation and is ideal for point-to-point use in large open areas such as base station installations or cellular backhaul. The included mounting bracket and hardware makes this antenna very easy to install. This LTE / CBRS Mesh Parabolic Dish antenna just like our wide selection of superior quality RF parts, ship same day. Contact our knowledgeable and friendly technical support and sales staff for your answers on antennas or other RadioWaves products.

Features

- Low Windload Mesh Design
- +/-45 Slant Polarization
- 20 dBi Gain
- 2x2 MIMO
- Type N Male Connector

Applications

- LTE,5G,CBRS
- Cellular networks
- DAS (Distributed Antenna Systems)
- IEEE 802.11b/g/n WiFi applications

SPECIFICATIONS

General

Antenna Type	Mesh Parabolic Reflector Antenna
Size, nominal	2 ft 0.6 m

Polarization	Dual
Standard RF Connector Type	N-Male

Electrical

Operating Frequency Band	1.71 - 2.69 GHz	3.3 - 4.2 GHz
Half Power Beamwidth, Horizontal	15 degrees	12 degrees
Half Power Beamwidth, Vertical	15 degrees	12 degrees
Front to Back Ratio (F/B)	25 dB	25 dB
Gain, Low Frequency	19 dBi	21 dBi
Gain, Mid Frequency	20 dBi	22 dBi

Gain, High Frequency	21 dBi	23 dBi
VSWR	2.0:1	2.0:1
Return Loss	-10 dB	-10 dB
Port to Port Isolation, Max (dB)	20 dB	
Input Power per Port, Max (Watts)	50 Watts	

Mechanical

Fine Elevation Adjustment	+/- 30 degrees
Mounting Pipe Diameter, Min	1.2 inch 3 cm
Mounting Pipe Diameter, Max	1.8 inch 5 cm
Net Weight	4.4 lbs 2 kg
Wind Velocity Operational	90 mph 145 km/h
Wind Velocity Survival Rating	125 mph 201 km/h

Mechanical Configuration	MPD2-1-7-NM
Axial Force (FA)	222 lbs 988 N
Side Force (FS)	14 lbs 62 N
Twisting Moment (MT)	225 ft-lbs 305 Nm
Operating Temperature Range	-40 to +60 C

Regulatory Compliance

Industry Canada Compliance	undeclared
RoHS-compliant	Yes

Shipping Information

Package Type	Cardboard
Gross Weight	6 lbs 2.7 kg

Dimensions, L x W x H	28 x 8 x 28in 71 x 20 x 71 cm
Shipping Volume	3.62 cu ft 0.1 cu m

TECHNICAL DRAWINGS

