0.6 m | 2 ft High Performance Parabolic Reflector Antenna, Single-polarized, 5.25-5.85GHz

HP2-5.2



The HP High Performance Series by RadioWaves offers a full line of high performance parabolic antennas engineered to provide ETSI class 2/3 radiation pattern performance as well as excellent gain. RadioWaves field-proven pre-assembled antennas and robust pole-mounts ensure “set and forget” installation with minimal post-installation maintenance. The included radome ensures robust and reliable performance under the most challenging conditions. If it’s rugged, it must be RadioWaves!

FEATURES AND BENEFITS
O High Performance ETSI Class 2/3* Parabolic Antennas – Excellent performance for a wide range of applications
O Fully Preassembled at the Factory – Simplifies installation on site and guarantees “factory-tested” quality

*ETSI Class depends on frequency band

SPECIFICATIONS

General

Antenna Type	High Performance Parabolic Reflector Antenna
Size, nominal	2 ft | 0.6 m
Polarization	Single

Standard RF Connector Type	N-Female
Standard RF Connector Suffix	NS (append suffix to model number)

Electrical

Operating Frequency Band	5.25 - 5.85 GHz
Half Power Beamwidth, Horizontal	6.1 degrees
Half Power Beamwidth, Vertical	6.1 degrees
Cross-Polarization Discrimination	28 dB
Front to Back Ratio (F/B)	44 dB

Gain, Low Frequency	28.3 dBi
Gain, Mid Frequency	28.8 dBi
Gain, High Frequency	29.3 dBi
VSWR	1.5:1
Return Loss	-14 dB

© 2023 Infinite Electronics, Inc. RadioWaves is a registered trademark of Infinite Electronics, Inc.
+1 (978) 459-8800 | sales@radiowaves.com | radiowaves.com

Mechanical

Fine Azimuth Adjustment	+/- 10 degrees
Fine Elevation Adjustment	+/- 30 degrees
Mounting Pipe Diameter, Min	2 inch | 5.08 cm
Mounting Pipe Diameter, Max	4.5 inch | 11.4 cm
Net Weight	27 lbs | 12.3 kg
Wind Velocity Operational	90 mph | 145 km/h
Wind Velocity Survival Rating	125 mph | 201 km/h

Mechanical Configuration	HP2
Axial Force (FA)	202 lbs | 899 N
Side Force (FS)	100 lbs | 445 N
Twisting Moment (MT)	194 ft-lbs | 263 Nm
Operating Temperature Range	-40 to +60 C
Max Pressure, PSIG, (if waveguide interface)	5

Regulatory Compliance

FCC	undeclared
Industry Canada Compliance	undeclared

ETSI	undeclared
RoHS-compliant	Yes

Shipping Information


Package Type	Cardboard
Gross Weight	48 lbs | 28.7 kg


Dimensions, L x W x H	31 x 31 x 25in | 79 x 79 x 64 cm
Shipping Volume	13.9 cu ft | 0.39 cu m


*Additional OEM interfaces and adapters may be available. Contact RadioWaves for a complete and current list of available adapters.

© 2023 Infinite Electronics, Inc. RadioWaves is a registered trademark of Infinite Electronics, Inc.
+1 (978) 459-8800 | sales@radiowaves.com | radiowaves.com

TECHNICAL DRAWINGS







HP2

© 2023 Infinite Electronics, Inc. RadioWaves is a registered trademark of Infinite Electronics, Inc.