

# HPD3-6

0.9 M | 3 FT HIGH PERFORMANCE PARABOLIC REFLECTOR ANTENNA, DUAL-POLARIZED, 5.725-7.125GHZ



## SPECIFICATIONS

### General

Antenna Type	High Performance Parabolic Reflector Antenna	Standard RF Connector Type	CPR137G
Size, nominal	3 ft   0.9 m	Standard RF Connector Suffix	RS (append suffix to model number)
Polarization	Dual		

### Electrical

Operating Frequency Band	5.725 - 7.125 GHz	Gain, Low Frequency	32 dBi
Half Power Beamwidth, Horizontal	3.7 degrees	Gain, Mid Frequency	33.1 dBi
Half Power Beamwidth, Vertical	3.7 degrees	Gain, High Frequency	34.1 dBi
Cross-Polarization Discrimination	28 dB	VSWR	1.37:1
Front to Back Ratio (F/B)	55 dB	Return Loss	-16.1 dB

### Mechanical

Fine Azimuth Adjustment	+/- 10 degrees	Mechanical Configuration	HP3
Fine Elevation Adjustment	+/- 10 degrees	Axial Force (FA)	403 lbs   1792 N
Mounting Pipe Diameter, Min	2.5 inch   5.1 cm	Side Force (FS)	200 lbs   890 N
Mounting Pipe Diameter, Max	4.5 inch   11.4 cm	Twisting Moment (MT)	344 ft-lbs   466 Nm
Net Weight	50 lbs   12.3 kg	Operating Temperature Range	-40 to +60 C
Wind Velocity Operational	90 mph   145 km/h	Max Pressure, PSIG, (if waveguide interface)	5
Wind Velocity Survival Rating	125 mph   201 km/h		

**Regulatory Compliance**

FCC	Part 101 Cat. B2
Industry Canada Compliance	Undeclared

ETSI	Undeclared
RoHS-compliant	Yes

**Shipping Information**

Package Type	Wood Crate
Gross Weight	143 lbs   69.8 kg

Dimensions, L x W x H	47 x 28 x 48in   119 x 71 x 122 cm
Shipping Volume	36.56 cu ft   1.04 cu m

\*Additional OEM interfaces and adapters may be available. Contact RadioWaves for a complete and current list of available adapters.

**TECHNICAL DRAWINGS**

