

1.8 m | 6 ft High Performance Parabolic Reflector Antenna, Single-polarized, 10.15-11.7GHz

## HP6-1011



The HP High Performance Series by RadioWaves offers a full line of high performance parabolic antennas engineered to provide ETSI class 2/3 radiation pattern performance as well as excellent gain. RadioWaves field-proven pre-assembled antennas and robust polemounts ensure "set and forget" installation with minimal post-installation maintenance. The included radome ensures robust and reliable performance under the most challenging conditions. If it's rugged, it must be RadioWaves!

#### FEATURES AND BENEFITS

O High Performance ETSI Class 2/3\* Parabolic Antennas – Excellent performance for a wide range of applications O Fully Preassembled at the Factory – Simplifies installation on site and guarantees "factory-tested" quality

\*ETSI Class depends on frequency band

### **SPECIFICATIONS**

#### General

Antenna Type	High Performance Parabolic Reflector Antenna
Size, nominal	6 ft   1.8 m
Polarization	Single

#### Electrical

Operating Frequency Band	10.15 - 11.7 GHz
Half Power Beamwidth, Horizontal	1.1 degrees
Half Power Beamwidth, Vertical	1.1 degrees
Cross-Polarization Discrimination	30 dB
Front to Back Ratio (F/B)	67 dB

Standard RF Connector Type	CPR90G
Standard RF Connector Suffix	RS (append suffix to model number)

Gain, Low Frequency	43.4 dBi
Gain, Mid Frequency	43.8 dBi
Gain, High Frequency	44.2 dBi
VSWR	1.37:1
Return Loss	-16.1 dB

 $\ensuremath{\mathbb{C}}$  2023 Infinite Electronics, Inc. RadioWaves is a registered trademark of Infinite Electronics, Inc.



### Mechanical

Fine Azimuth Adjustment	+/- 10 degrees
Fine Elevation Adjustment	+/- 10 degrees
Mounting Pipe Diameter, Min	4.5 inch   11.4 cm
Mounting Pipe Diameter, Max	4.5 inch   11.4 cm
Net Weight	251 lbs   113 kg
Wind Velocity Operational	90 mph   145 km/h
Wind Velocity Survival Rating	125 mph   201 km/h

Mechanical Configuration	HP6
Axial Force (FA)	1680 lbs   7473 N
Side Force (FS)	832 lbs   3700 N
Twisting Moment (MT)	2100 ft-lbs   2847 Nm
Operating Temperature Range	-40 to +60 C
Max Pressure, PSIG, (if waveguide interface)	5

## **Regulatory Compliance**

FCC	Part 101 Cat. A
Industry Canada Compliance	SRSP310.5, SRSP310.7 B

Shi	pping	Information
<b>U</b>	pping	mornation

Package Type	Wood Crate
Gross Weight	401 lbs   181.8 kg

Dimensions, L x W x H	77 x 35 x 80in   195 x 89 x 203 cm
Shipping Volume	124.77 cu ft   3.53 cu m

302217 R1 C2

Yes

\*Additional OEM interfaces and adapters may be available. Contact RadioWaves for a complete and current list of available adapters.

ETSI

RoHS-compliant



# **TECHNICAL DRAWINGS**

